

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/033799 A1

(51) International Patent Classification⁷: E01C 5/00, 5/06,
5/22, E04F 15/08, B44C 1/28, B28B 7/16

(21) International Application Number:
PCT/AU2003/001345

(22) International Filing Date: 10 October 2003 (10.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002952043 10 October 2002 (10.10.2002) AU

(71) Applicant and

(72) Inventor: BOSERIO, Brian, Augustine [AU/AU];
Whumbal Creek, Peninsula Development Road via, MA-
REEBA, Queensland 4880 (AU).

(74) Agent: FISHER ADAMS KELLY; Level 13 AMP Place,
10 Eagle Street, BRISBANE, Queensland 4000 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: METHODS FOR MAKING COMPOSITE TILES



(57) **Abstract:** A decorative paving tile or panel comprises a plurality of irregularly shaped stone elements of the same or differing thickness embedded in a backing layer or base to form a tile or panel of the predetermined thickness wherein the normally exposed surfaces of said stone elements lie in a plane substantially parallel to a mounting surface of said backing layer or base. A flowable displacement material may be employed in the interstices between adjacent stone elements and/or a boundary wall of a tile or panel mould to form a grouting channel. An irregular space between adjacent stone elements of adjacent tiles or panels allows the formation of an optically seamless tiled or panelled surface when grouted.

WO 2004/033799 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.